

OPT155-852xxxR

155Mb/s 1x9 Optical Transceiver, Multimode, 850nm, 2km, Duplex SC/ST/FC

Features

- Up to 155Mb/s data links
- Industry Standard 1×9 package
- Duplex SC, ST or FC connector
- Single +3.3V or +5V Power Supply
- Operating wavelength 850nm
- Up to 2 km over multi-mode fiber
- Standard PECL or LVPECL data output with signal detect indication
- Class 1 laser safety standard IEC 60825 compliant
- ROHS compliant and Lead Free
- Operating case temperature: Standard: 0 to +70°C, Industrial: -40 to +85°C



Applications

- ATM 155 Mbps Links
- SONET OC-3 & SDH STM-1
- Fast Ethernet 100 Mb/s Links
- Fast Ethernet to Fiber media converters
- Industrial grade for industrial hardened Ethernet
- Digital video transmission system

Description

The OPT155-852xxxR series is the high performance and cost-effective multi-mode 1×9 optical transceiver for serial optical communication applications. They are suitable for 100Mb/s Fast Ethernet, SDH STM-1, SONET OC-3 and ATM (Asynchronous Transfer Mode) designs at the 155Mb/s rate. This series 1x9 transceiver module provides 2km transmission distance over multimode fiber at a nominal wavelength of 850nm.

Each 1×9 transceiver module consists of a transmitter section and a receiver section. The transmitter incorporates a highly reliable 850 nm VCSEL and a driver circuit which converts Pseudo Emitter Coupled Logic(PECL) data to light signal, the receiver incorporates an efficient InGaAs/InP PIN photodiode converting the light signal into an electrical current which is amplified and regenerated into PECL compatible data.

The 155Mbps 1×9 multimode 850nm 2km transceiver provides with choice of duplex SC, FC or ST connector for the different client. The OPT155-852xxxR family also provide the commercial grade for commonly application, and industrial grade for industrial hardened environment application such as industrial Ethernet Switch, Industrial computing, Industrial Ethernet media converters and so on. They are compliant with class 1 FDA, IEC60825-1 laser safety and RoHS.

Absolute Maximum Ratings

Parameter	Symbol	Min	Max	Unit	Note
Storage Temperature	Ts	-40	85	°C	-
Power Supply Voltage	Vcc (3.3V)	0.5	4.0	V	OPT155-8523xxR

	V _{cc} (5V)	0.5	6.0	V	OPT155-8525xxR
Soldering Temperature	-	-	260	°C	10 seconds on leads only
Input Voltage	V _{in}	GND	V _{cc}	V	-

Recommended Operating Conditions

Parameter	Symbol	Min.	Typ.	Max.	Units
Power Supply Voltage	V _{cc}	3.1	3.3	3.5	V
		4.75	5	5.25	
Operating Temperature	Standard	0	-	70	°C
	Industrial	-40	-	85	°C
Data Rate	-	-	155	-	Mbps
Power Supply Current	I _{cc}	-	150	250	mA

Transmitter Specifications (0°C < T_{op} < 70°C)

Parameter	Symbol	Min.	Typ.	Max.	Units
Optical					
Optical Transmit Power	P _o	-10	-	-3	dBm
Optical Center Wavelength	λ _c	830	850	860	nm
Output Spectrum Width	Δλ	-	-	0.85	nm (RMS)
Extinction Ratio	E _R	10.0	-	-	dB
Output Eye	Compliant with ITU recommendation G.957 STM-1/OC-3				
Optical Rise Time	t _r	-	-	2	ns
Optical Fall Time	t _f	-	-	2	ns
Electrical					
Differential Input Voltage	V _{IH-VIL}	0.3	-	2.2	V
Common-mode Input Voltage	V _{COM-VCC}	-1.38	-	-0.47	V
PECL Output Voltage-Low	V _{OL-VCC}	-1.810	-	-1.620	V
PECL Output Voltage-High	V _{OH-VCC}	-1.025	-	-0.880	V

Receiver Specifications (0°C < T_{op} < 70°C)

Parameter	Symbol	Min.	Typ.	Max.	Units
Optical					
Sensitivity	Sen	-	-	-30	dBm
Maximum Input	P _{MAX}	-3	-	-	dBm

Power(Saturation)					
Signal Detect – Asserted	P_a	-	-	-30	dBm
Signal Detect – Deasserted	P_d	-45	-	-	dBm
Signal Detect – Hysteresis	P_{hys}	1	-	4	dB
Wavelength of Operation	λ	760	-	860	nm
Electrical					
Data Output Voltage – Low	$V_{IL}-V_{CC}$	-1.83	-	-1.555	V
Data Output Voltage – High	$V_{IH}-V_{CC}$	-1.085	-	-0.88	V
Signal Detect Output Voltage - Low	$V_{SIL}-V_{CC}$	-2.0	-	-1.58	V
Signal Detect Output Voltage -High	$V_{SIH}-V_{CC}$	-1.1	-	-0.74	V

Pin Assignment




Figure 1. Pin-Out

Mechanical Dimensions




Figure 2. SC Connector




Figure 3. FC Connector




Figure 4. ST Connector

Ordering information

Part number	Description
OPT155-8523SCR	155Mb/s 1x9 Transceiver,MMF,850nm,2km,3.3V,SC

OPT155-8523TCR	155Mb/s 1x9 Transceiver,MMF,850nm,2km,3.3V,ST
OPT155-8523FCR	155Mb/s 1x9 Transceiver,MMF,850nm,2km,3.3V,FC
OPT155-8525SCR	155Mb/s 1x9 Transceiver,MMF,850nm,2km,5V,SC
OPT155-8525TCR	155Mb/s 1x9 Transceiver,MMF,850nm,2km,5V,ST
OPT155-8525FCR	155Mb/s 1x9 Transceiver,MMF,850nm,2km,5V,FC
OPT155-8523STR	155Mb/s 1x9 Industrial Transceiver,MMF,850nm,2km,3.3V,SC,-40~+85°C
OPT155-8523TTR	155Mb/s 1x9 Industrial Transceiver,MMF,850nm,2km,3.3V,ST,-40~+85°C
OPT155-8523FTR	155Mb/s 1x9 Industrial Transceiver,MMF,850nm,2km,3.3V,FC,-40~+85°C
OPT155-8525STR	155Mb/s 1x9 Industrial Transceiver,MMF,850nm,2km,5V,SC,-40~+85°C
OPT155-8525TTR	155Mb/s 1x9 Industrial Transceiver,MMF,850nm,2km,5V,ST,-40~+85°C
OPT155-8525FTR	155Mb/s 1x9 Industrial Transceiver,MMF,850nm,2km,5V,FC,-40~+85°C

Warnings

Process plug

The transceiver optics is supplied with a dust cover. This plug protects the transceiver optics during standard manufacturing processes by preventing contamination from air borne particles.It is recommended that the dust cover remain in the transceiver whenever an optical fiber connector is not inserted.

Handling Precautions

The transceiver optics is susceptible to damage as a result of electrostatic discharge (ESD). A static free environment is highly recommended. Follow guidelines according to proper ESD procedures.

Laser Safety

The transceiver optics is a Class 1 laser product per international standard IEC 60825-1. Radiation emitted by laser devices can be dangerous to human eyes. Avoid eye exposure to direct or indirect radiation.

For more product information, visit us on the web at www.optcore.net



DS/VER180203/EN Copyright © 2018 Optcore Technology Co.,Ltd. All rights reserved. Optcore, Optcore logo are registered trademarks of Optcore Technology Co.,Ltd. All other brands, product names, or trademarks mentioned are the property of their respective owners. Specifications and product availability are subject to change without notice. Optcore assumes no responsibility for inaccuracies contained herein.

